

L Number	Hits	Search Text	DB	Time stamp
1	272	(623/21.18,20.15,20.29,20.33,22.18,23.41,14	USPAT&CLS. US-PGPUB; EPO; JPO; DERWENT USPAT;	2003/12/15 11:02
2	10	(("5871545") or ("5871542") or ("5246460") or ("5226919") or ("5314482")).PN.	US-PGPUB; EPO; JPO; DERWENT	2003/12/15 11:06
3	8	(("4309778") or ("4471158") or ("5766259")).PN.	USPAT; US-PGPUB; EPO; JPO; DERWENT	2003/12/15 11:07
4	8	(("4309778") or ("4470158") or ("5766259")).PN.	USPAT; US-PGPUB; EPO; JPO; DERWENT	2003/12/15 11:07
5	9	("3872519" "3987500" "4156944" "4232404" "4340978" "4470158" "4755185" "5122144" "5326365").PN.	USPAT	2003/12/15 11:11
6	2	5766259.URPN.	USPAT	2003/12/15 11:18
7	11	("Re29757" "3869731" "4001896" "4016606" "4021864" "4040131" "4081866" "4085466" "4207627" "4209861" "4224697").PN.	USPAT	2003/12/15 11:19
8	52	4309778.URPN.	USPAT	2003/12/15 11:24

Document ID	KSC	Issue Date	Page	Title
1 US 5906643 A	U	19990525	8	Stabilised m
2 US 3872519 A	U	19750325	6	Total ankle

US005906643A

United States Patent [19]

Walker

[11] Patent Number: 5,906,643

[45] Date of Patent: May 25, 1999

[54] STABILISED MOBILE BEARING KNEE

5,370,701	12/1994	Fitz	623/20
5,387,240	2/1995	Potegow et al.	623/20
5,395,403	3/1995	Boller	623/20
5,409,039	3/1995	Walker	623/20
5,438,342	8/1997	Dragooch et al.	623/20
5,483,466	11/1997	Peppas	623/20

[21] Appl. No.: 08/817,263

FOREIGN PATENT DOCUMENTS

[22] PCT Filed: Jul. 27, 1995

G 981 352 A1	8/1990	European Pat. Off. .
G 510 229 A1	10/1992	European Pat. Off. .
G 637 229 A2	12/1994	European Pat. Off. .
WO 94/26212	12/1994	WIPO .

[56] PCT No.: PCT/GB95/01781

[1371 Date: Apr. 14, 1997

[102(e) Date: Apr. 14, 1997

[67] PCT Pub. No.: WO96/03097

PCT Pub. Date: Feb. 8, 1996

[30] Foreign Application Priority Data

[31] Appl. No.: United Kingdom

[32] Int. Cl. 4

[33] U.S. Cl.

[58] Field of Search

U.S. PATENT DOCUMENTS

[4,224,597] 9/1980 Murray et al.

[5,116,375] 5/1992 Hofmann

[5,314,483] 5/1994 Weiland et al.

[5,330,534] 7/1994 Hernigosa et al.

[5,370,699] 12/1994 Hood et al.

References Cited

A prosthesis for total knee replacement (TKR) includes a femoral component having a pair of condylar-bearing surfaces (10,12), a tibial component having a tibial platform (22) with an upstanding abutment (18) located between the condylar-bearing surfaces, and a meniscal component (16) interposed between the condylar-bearing surfaces and the tibial platform for sliding movement in the anterior-posterior (A-P) direction. The femoral component has an unicondylar projecting surface (20) adapted to contact the upstanding abutment at high degrees of flexion so as to influence the sliding movement of the meniscal component in a posterior direction.

12 Claims, 4 Drawing Sheets

